




HIGH PERFORMANCE BIFACIAL PERC MONOCRYSTALLINE MODULE

Draft



RSM120-8-580BMDG-600BMDG

120 CELL Mono PERC Module	580-600Wp Power Output Range
1500VDC Maximum System Voltage	21.2% Maximum Efficiency

KEY SALIENT FEATURES

- Bloomberg TIER 1** Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing
- Bifacial** Bifacial technology enables additional energy harvesting from rear side (up to 30%)
- Thermometer icon** Industry leading lowest thermal co-efficient of power
- 12 years** Industry leading 12 years product warranty
- Sun and cloud icon** Excellent low irradiance performance
- PID** Excellent PID resistance
- +** Positive tight power tolerance
- 2 EL** Dual stage 100% EL Inspection warranting defect-free product
- Module Imp binning icon** Module Imp binning radically reduces string mismatch losses
- Warranty icon** Warranted reliability and stringent quality assurances well beyond certified requirements
- Snowflake icon** Certified to withstand severe environmental conditions
 - ♦ Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
 - ♦ Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
 - ♦ Excellent mechanical resistance: wind load 2400Pa & snow load 5400Pa




RISEN ENERGY CO., LTD.

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

Tashan Industry Zone, Meilin, Ninghai 315609, Ningbo | PRC
Tel: +86-574-59953239 Fax: +86-574-59953599
E-mail: marketing@risenenergy.com Website: www.risenenergy.com

LINEAR PERFORMANCE WARRANTY

12 year Product Warranty / 30 year Linear Power Warranty



★ Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd





Preliminary
For Global Market

THE POWER OF RISING VALUE


Dimensions of PV Module

Unit: mm




RSM120-8-590BMDG

I-V characteristics at different irradiances



I-V characteristics at different temperatures

(AM1.5, 1000W/m²)



Our Partners:

REM120-BMDG-12BB-EN-H2-5-2020

ELECTRICAL DATA (STC)

Model Number	RSM120-8-580BMDG	RSM120-8-585BMDG	RSM120-8-590BMDG	RSM120-8-595BMDG	RSM120-8-600BMDG
Rated Power in Watts-Pmax(Wp)	580	585	590	595	600
Open Circuit Voltage-Voc(V)	40.90	41.10	41.30	41.50	41.70
Short Circuit Current-Isc(A)	18.06	18.11	18.16	18.21	18.26
Maximum Power Voltage-Vmpp(V)	34.04	34.22	34.42	34.60	34.80
Maximum Power Current-Impp(A)	17.05	17.10	17.15	17.20	17.25
Module Efficiency (%) *	20.5	20.7	20.8	21.0	21.2

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.
Bifacial factor: 70%±5 * Module Efficiency (%): Round-off to the nearest number

Electrical characteristics with 10% rear side power gain

	638	644	649	655	660
Total Equivalent power -Pmax (Wp)	638	644	649	655	660
Open Circuit Voltage-Voc(V)	40.90	41.10	41.30	41.50	41.70
Short Circuit Current-Isc(A)	19.87	19.92	19.98	20.03	20.09
Maximum Power Voltage-Vmpp(V)	34.04	34.22	34.42	34.60	34.80
Maximum Power Current-Impp(A)	18.76	18.81	18.87	18.92	18.98

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

ELECTRICAL DATA (NMOT)

Model Number	RSM120-8-580BMDG	RSM120-8-585BMDG	RSM120-8-590BMDG	RSM120-8-595BMDG	RSM120-8-600BMDG
Maximum Power-Pmax (Wp)	439.5	443.1	447.0	450.7	454.6
Open Circuit Voltage-Voc (V)	38.04	38.22	38.41	38.60	38.78
Short Circuit Current-Isc (A)	14.81	14.85	14.89	14.93	14.97
Maximum Power Voltage-Vmpp (V)	31.59	31.76	31.94	32.11	32.29
Maximum Power Current-Impp (A)	13.91	13.95	13.99	14.04	14.08

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Monocrystalline
Cell configuration	120 cells (6×10+6×10)
Module dimensions	2172×1303×35mm
Weight	35kg
Superstrate	High Transmission, Low Iron, Tempered ARC Glass
Substrate	Tempered Glass
Frame	Anodized Aluminium Alloy type 6005-2T6, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² (12AWG), Positive(+)350mm, Negative(-)350mm (Connector Included)
Connector	Risen Twinsel PV-SY02, IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	0.04%/°C
Temperature Coefficient of Pmax	-0.34%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	40A
Limiting Reverse Current	40A

PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	527
Number of modules per pallet	31
Number of pallets per container	17
Box gross weight[kg]	1100

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2020 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.

THE POWER OF RISING VALUE